



# Energy Wall U-ERV 1200 Series

U-ERV 1200 Standard Features		Industry Standard Comparison
Airflow Range:	0 to 1600 CFM [1200 Rated]	Full Variable ECM+ Remote Fan Modulation
Dimensions:	54" L X 32" D X 24" Height	2-4X Smaller Size (12" Height per module)
Ultra Lightweight:	196 lbs.	2.5X Lighter (Varies by Options) (98 lbs. per module)
AHRI 1060 Tested Core:	EWT-11-42 QTY(2) HWT-11-42 QTY(2)	Patented Static Plate, heat and humidity transfer Static Plate, heat transfer or condensing wrap-around application
Sensible Efficiency:	73% @ 1200 SCFM	Up to 90% Possible
Latent Efficiency:	63% @ 1200 SCFM	Up to 70% Possible
Total Efficiency:	69% @ 1200 SCFM	Up to 80% Possible
Coil Option:	36,190 BTUs/Hr	Dx or Chilled Water. VRF Integrated.
Exhaust Air Transfer:	Zero	Good for Bathroom Exhaust, Laboratories, Hospitals
Cost:	Lowest Installed	Lower transport, installation, maintenance, and fan energy costs
Minimal Maintenance:	Filters @ 3-6 months	Total qty. 2, MERV 11: 5.00"x40.38"x1.88" (Actual Size) (Per Module)
Stack Multiple Modules:	Vertical or Horizontal	Patented design - a single duct will connect to multiple U-ERVs
Fan Motors:	ECM+ IP68 Rated	Variable Airflow adjustability & balancing with mechanical turn potentiometers Remote Variable Airflow adjustability via 0-10V signal
Antimicrobial Membrane:	Salt / Ceramic	Proven highly antimicrobial without the addition of additives
Like a UV Light:	MERV 11 Equivalence	Actively kills bacteria flowing with both airstreams
Non-Fused Disconnect:	UL98 Rated	Lowers Installed Cost - Defeatable Lockout For Safe Access
Safety:		
Duct Connections:		Self tapping screws with duct sealant. Connect to Fan Cube or Unit port
Application:	Any Orientation	Universal Compatibility for Bolt-on, Roof-top, Exterior, or Interior Installation
Electrical Power:	Universal Input AC or DC	90 to 264 VAC Input (50/60Hz) or 40 to 370 VDC Input
Extreme Exterior Shell:	Gray Polypropylene	Corrosion Proof, double wall construction with fumed silica insulation

U-ERV 1200 Series Model Numbers										
Model Number	Type	External Static Pressure @ 1200 SCFM			90 to 264 VAC Input (50/60 Hz)			40 to 350 VDC Input		
		Supply (in. w.g.)	Exhaust (in. w.g.)	Weight (lbs.)	120 VAC 1Ø(Amps)	230 VAC 1Ø(Amps)	208 VAC 3Ø(Amps)	55.2 VDC (Amps)	255 VDC (Amps)	350 VDC (Amps)
UERV 1200LL	Enthalpy	0.5	0.5	196	18.2	9.5	10.5	20	6.8	5
UERV 1200HH	Enthalpy	2.5	2.5	212	36.4	19	21.0	40	13.6	10
UERV 1200LH	Enthalpy	0.5	2.5	204	27.3	14.25	15.75	30	10.2	7.5
UERV 1200HL	Enthalpy	2.5	0.5	204	27.3	14.25	15.75	30	10.2	7.5
UHRV 1200LL	Sensible	0.5	0.5	196	18.2	9.5	10.5	20	6.8	5
UHRV 1200HH	Sensible	2.5	2.5	212	36.4	19	21.0	40	13.6	10
UHRV 1200LH	Sensible	0.5	2.5	204	27.3	14.25	15.75	30	10.2	7.5
UHRV 1200HL	Sensible	2.5	0.5	204	27.3	14.25	15.75	30	10.2	7.5

Note: Minimum 180VAC and 255VDC Recommended to Achieve Rated Static Pressure

# Energy Wall U-ERV 1200 Series



1002 New Holland Ave  
Lancaster PA 17601  
www.energywall.com